

# GUARDIAN

## AIR AND MOISTURE BARRIER

# Green



**GUARDIAN** is a high elongation elastomer, manufactured from 100% acrylic resins, which achieves outstanding adhesion to wood, stucco, concrete and gypsum surfaces. **GUARDIAN**, when applied in combination with **GUARDIAN JOINT SEALANT**, performs as the primary air and moisture barrier for the **EIFS** water managed system.

**WEATHER CONDITIONS:** Cure time will depend on application thickness, humidity, and temperature. Apply only when temperatures are a minimum of 40°F (4°C) and rising. See Technical Data for additional weather precautions.

**CAUTION! CAN CAUSE IRRITATION OF NOSE, THROAT AND LUNGS. CAN CAUSE NAUSEA AND HEADACHE.** Prolonged or repeated breathing of vapor or spray mist may be harmful. Use a respirator for protection from vapor or spray mist. Avoid eye and skin contact. Do not take internally. Wash thoroughly after handling and before eating or smoking. Keep container closed when not in use.

**FIRST AID:** If swallowed, do **not** induce vomiting. Call a physician immediately. Never give anything by mouth to an unconscious person. In case of eye contact, flush with clean water for 15 minutes, lifting eyelids to permit thorough flushing. If irritation develops, consult a physician. For skin contact, wash with soap and water, then flush with water for 15 minutes. If irritation develops, consult a physician. Remove contaminated clothing and shoes. Wash clothing before reuse. Clean contaminated shoes. If inhaled, move to fresh air. Give oxygen or artificial respiration as needed. Call a physician immediately. For additional information, see Material Safety Data Sheet (MSDS) for this material. Contains: Name/C.A.S.#: Acrylic Polymer. . .N/A, Calcium Carbonate. . 1317-65-3, Titanium Dioxide 13463-67-7.

**Use Only In A Well Ventilated Area**  
**KEEP OUT OF REACH OF CHILDREN**  
**FOR PROFESSIONAL USE ONLY**

### EIFS JAPAN, INC.

Japan :  
1-7 Aobadai, Kakegawa-city,  
Shizuoka 436-0019  
Tel : (0537)23-3992  
[www.eifsjapan.com](http://www.eifsjapan.com)

U.S.A.:  
389 Kevin Ct SE.,  
Salem, OR 97306  
Tel : (503)581-1032  
E-mail : [usa@eifsjapan.com](mailto:usa@eifsjapan.com)

# G.J.S

## Guardian Joint Sealant



**GUARDIAN JOINT SEALANT** is a water-based, high solids elastomeric sealant utilizing the latest advances in 100% acrylic technology. Its thick, butter consistency allows it to be easily trowled on both vertical and horizontal surfaces. **GUARDIAN JOINT SEALANT** is manufactured from a unique acrylic resin, specifically designed to provide increased tensile strength and elongation. It has excellent adhesion to wood, exterior gypsum sheathing, concrete and metal.

**GUARDIAN JOINT SEALANT** will freeze and become unusable at temperatures below 32°F (0°C). Do not store or ship material if there is a possibility of freezing temperatures. Do not apply if **GUARDIAN JOINT SEALANT** cannot cure prior to freezing temperatures, rain or heavy dew. See separate Material Safety Data Sheet for additional precautions.

**CAUTION! CAN CAUSE IRRITATION OF NOSE, THROAT AND LUNGS. CAN CAUSE NAUSEA AND HEADACHE.** Prolonged or repeated breathing of vapor or spray mist may be harmful. Use a respirator for protection from vapor or spray mist. Avoid eye and skin contact. Do not take internally. Wash thoroughly after handling and before eating or smoking. Keep container closed when not in use.

**FIRST AID:** If swallowed do **not** induce vomiting. Call a physician immediately. Never give anything by mouth to an unconscious person. In case of eye contact, flush with clean water for 15 minutes, lifting eyelids to permit thorough flushing. If irritation develops, consult a physician. For skin contact, wash with soap and water, then flush with water for 15 minutes. If irritation develops, consult a physician. Remove contaminated clothing and shoes. Wash clothing before reuse. Clean contaminated shoes. If inhaled, move to fresh air. Give oxygen or artificial respiration, as needed. Call a physician immediately. For additional information, see Material Safety Data Sheet (MSDS) for this material. Contains: Name/C.A.S.#: Acrylic Polymer. . .N/A, Calcium Carbonate. . .471-34-1, Titanium Dioxide. . .13463-67-7, Petroleum Derivatives. . .N/A, Isobutane (Encapsulated in Polymer). . .78-28-5.

**Use Only In A Well Ventilated Area**  
**KEEP OUT OF REACH OF CHILDREN**  
**FOR PROFESSIONAL USE ONLY**

### EIFS JAPAN, INC.

Japan :  
1-7 Aobadai, Kakegawa-city,  
Shizuoka 436-0019  
Tel : (0537)23-3992  
www.eifsjapan.com

U.S.A.:  
389 Kevin Ct SE.,  
Salem, OR 97306  
Tel : (503)581-1032  
E-mail : usa@eifsjapan.com